



PF11MF/PF12MF

PANEL FASTENERS



Knob: Aluminum
 Retainer: Aluminum
 Screw: 300 or 400 Series Stainless Steel
 Spring: 300 Series Stainless Steel

Part Number Designation



All dimensions are in inches (Size Unit:inch)

	Thread Size	Type		Thread Code	Shank Code	A MAX.	Min. Sheet Thickness	Hole size In Sheet +.005	C MAX.	E +.010	G ±.025	P ±.025	T1 Nom.	T2 Nom.	Driver Size
		Knurled Cap	Smooth Code												
IMPERIAL	.112-.40 (#4-40)	PF11MF	PF12MF	440	0	.041	.031	.187	.186	.417	.170	.000	.310	.450	#1
					1						.230	.055			
					2						.290	.115			
	.138-.32 (#6-32)	PF11MF	PF12MF	632	0	.072	.060	.213	.212	.450	.230	.000	.450	.640	#2
					1						.290	.024			
					2						.350	.084			
	.164-.32 (#8-32)	PF11MF	PF12MF	832	0	.072	.060	.266	.265	.514	.230	.000	.450	.640	#2
					1						.290	.024			
					2						.350	.084			
	.190-.32 (#10-32)	PF11MF	PF12MF	032	0	.072	.060	.266	.265	.514	.230	.000	.450	.640	#2
					1						.290	.024			
					2						.350	.084			
.250-.20 (1/4-20)	PF11MF	PF12MF	0420	0	.072	.060	.323	.322	.575	.290	.000	.530	.790	#3	
				1						.350	.024				
				2						.410	.084				

All dimensions are in millimeters (Size Unit:mm)

	Thread Size	Type		Thread Code	Shank Code	A MAX.	Min. Sheet Thickness	Hole size In Sheet +0.08	C MAX.	E +0.25	G ±0.64	P ±0.64	T1 Nom.	T2 Nom.	Driver Size
		Knurled Cap	Smooth Code												
METRIC	M3X0.5	PF11MF	PF12MF	M3	0	1.05	0.79	4.75	4.73	10.59	4.32	0	7.87	11.43	#1
					1						5.84	1.40			
					2						7.37	2.92			
	M3.5X0.6	PF11MF	PF12MF	M3.5	0	1.83	1.52	5.40	5.38	11.43	.584	0	11.43	16.26	#2
					1						7.37	0.61			
					2						8.89	2.13			
	M4X0.7	PF11MF	PF12MF	M4	0	1.83	1.52	6.76	6.74	13.06	.584	0	11.43	16.26	#2
					1						7.37	0.61			
					2						8.89	2.13			
	M5X0.8	PF11MF	PF12MF	M5	0	1.83	1.52	6.76	6.74	13.06	.584	0	11.43	16.26	#2
					1						7.37	0.61			
					2						8.89	2.13			
M6X1	PF11MF	PF12MF	M6	0	1.83	1.52	8.2	8.18	14.61	.737	0	13.46	20.07	#3	
				1						8.89	0.61				
				2						10.41	2.13				