


## PF50/PF60


### PANEL FASTENERS



#### Part Number Designation



Knob: Carbon Steel  
Screw: Carbon Steel  
Ferrule: Carbon Steel  
Spring: 300 Series Stainless Steel



All dimensions are in inches (Size Unit: inch)

Thread Size	Type		Thread Code	Shank Code	A (Shank) Max.	Min. Sheet Thickness	Hole size In Sheet +.003	C MAX.	E +.015 - .005	H ±.008	G ±.025	P ±.025	T1 MAX.	T2 Nom.	Driver Size	Min. Dist Hole C/L To Edge
	Knurled Cap	Stainless Steel														
112-40 (#4-40)	PF50	PF60	440	0	.030	.030	.203	.202	.406	.207	.230	.000	.340	.520	#1	.26
	PF50A	PF60A		1	.038	.040	.203	.202	.406	.207	.230	.000	.340	.520		
	PF50B	PF60B		0	.058	.060	.203	.202	.406	.207	.230	.000	.340	.520		
138-32 (#6-32)	PF50	PF60	632	0	.030	.030	.219	.218	.438	.207	.230	.000	.340	.520	#2	.28
	PF50A	PF60A		1	.038	.040	.219	.218	.438	.207	.230	.000	.340	.520		
	PF50B	PF60B		0	.058	.060	.219	.218	.438	.207	.230	.000	.340	.520		
164-32 (#8-32)	PF50	PF60	832	0	.030	.030	.250	.249	.468	.217	.230	.000	.340	.520	#2	.29
	PF50A	PF60A		1	.038	.040	.250	.249	.468	.217	.230	.000	.340	.520		
	PF50B	PF60B		0	.058	.060	.250	.249	.468	.217	.230	.000	.340	.520		
190-32 (#10-32)	PF50	PF60	032	0	.030	.030	.312	.311	.530	.225	.230	.000	.360	.530	#2	.33
	PF50A	PF60A		1	.038	.040	.312	.311	.530	.225	.230	.000	.360	.530		
	PF50B	PF60B		0	.058	.060	.312	.311	.530	.225	.230	.000	.360	.530		
250-20 (#14-20)	PF50	PF60	0420	0	.058	.060	.375	.374	.625	.246	.260	.000	.395	.600	#2	.38

All dimensions are in millimeters (Size Unit: mm)

Thread Size	Type		Thread Code	Shank Code	A (Shank) Max.	Min. Sheet Thickness	Hole size In Sheet +0.08	C MAX.	E +0.4 -0.13	H ±0.2	G ±0.64	P ±0.64	T1 MAX.	T2 Nom.	Driver Size	Min. Dist Hole C/L To Edge
	Knurled Cap	Stainless Steel														
M3X0.5	PF50	PF60	M3	0	0.77	0.8	5.5	5.48	10.3	5.26	5.84	0	8.64	13.21	#1	6.6
	PF50A	PF60A		1	0.97	1	5.5	5.48	10.3	5.26	5.84	1.32	8.64	13.21		
	PF50B	PF60B		0	1.47	1.5	5.5	5.48	10.3	5.26	5.73	0.81	8.64	13.21		
M3.5X0.6	PF50	PF60	M3.5	0	0.77	0.8	5.56	5.54	11.1	5.26	5.84	0	8.64	13.21	#2	7.1
	PF50A	PF60A		1	0.97	1	5.56	5.54	11.1	5.26	5.84	1.32	8.64	13.21		
	PF50B	PF60B		0	1.47	1.5	5.56	5.54	11.1	5.26	5.73	0.81	8.64	13.21		
MAX0.7	PF50	PF60	M4	0	0.77	0.8	6.4	6.38	11.9	5.51	7.37	0	8.64	13.46	#2	7.4
	PF50A	PF60A		1	0.97	1	6.4	6.38	11.9	5.51	7.37	1.32	8.64	13.46		
	PF50B	PF60B		0	1.47	1.5	6.4	6.38	11.9	5.51	7.37	0.81	8.64	13.46		
MAX0.8	PF50	PF60	M5	0	0.77	0.8	8	7.98	13.5	5.72	5.84	0	9.15	13.46	#2	8.4
	PF50A	PF60A		1	0.97	1	8	7.98	13.5	5.72	7.37	1.32	9.15	13.46		
	PF50B	PF60B		0	1.47	1.5	8	7.98	13.5	5.72	7.37	0.81	9.15	13.46		
M6X1	PF50	PF60	M6	0	1.47	1.5	9.5	9.48	15.9	6.25	8.64	1.52	10.04	15.24	#2	9.7