



PFHV

PANEL FASTENER




Part Number Designation



Retainer: Heat-treated Carbon Steel

Screw: Heat-treated Carbon Steel



All dimensions are in inches (Size Unit: inch)

	Thread Size	Type	Thread Code	Shank Code	A (Shank) Max.	Min. Sheet Thickness	Hole size in Sheet +.003	C MAX.	E ± .010	H ± .005	G ± .025	P ± .025	T1 Nom.	T2 Nom.	Driver Size	Min. Dist Hole C/L To Edge
UNIFIED	.112-.40 (#4-40)	PFHV	440	0 1	.036	.036	.203	.202	.260	.080	.216 -.316	.000 .095	.260	.436	#1	.250
	.138-.32 (#6-32)	PFHV	632	0 1	.036	.036	.219	.218	.276	.092	.234 .350	.000 .120	.290	.484	#2	.280
	.164-.32 (#8-32)	PFHV	832	0 1	.036	.036	.252	.251	.309	.111	.259 .371	.000 .106	.335	.555	#2	.26

All dimensions are in millimeters (Size Unit: mm)

	Thread Size	Type	Thread Code	Shank Code	A (Shank) Max.	Min. Sheet Thickness	Hole size in Sheet +0.08	C MAX.	E ± 0.25	H ± 0.13	G ± 0.64	P ± 0.64	T1 Nom.	T2 Nom.	Driver Size	Min. Dist Hole C/L To Edge
METRIC	M3 x 0.5	PFHV	M3	0 1	0.92	0.92	5.5	5.49	6.95	2.03	5.55 7.56	0 1.9	6.69	11.25	#1	5.8
	M3.5 x 0.6	PFHV	M3.5	0 1	0.92	0.92	6.0	5.98	7.45	2.34	6.01 8.42	0 2.3	7.45	12.47	#2	6.3
	M4 x 0.7	PFHV	M4	0 1	0.92	0.92	6.4	6.38	7.85	2.79	6.59 9.39	0 2.7	8.5	14.1	#2	6.7